

GEO HOT WEDGE WELDER WIN-GM2



PRODUCT INFORMATION

Geo Hot Wedge Welder WIN-GM2

It adopts advanced hot wedge structure. With its high power, high speed and pressure, it welds 0.2mm -2.0mm thickness hot melting materials. LST-GM2 is of welding way towards one edge. This machine is specially designed for water conservancy, aquaculture, landfills, chemical mining, sewage treatment, roof constructions and other waterproofing projects.



SPECIFICATIONS

Model	WIN – GM2
Rated Voltage	230V/120V
Rated Power	600W
Frequency	50/60HZ
Heating Temperature	50~450
Welding Speed	0.5-5.0m/min
Welding pressure	100-1000N
Material Thickness Welded	0.2mm-2.0mm single layer
Seam Width	15mm*2, Interior Cavity 15mm customized
Weld Strength	≥ 85%material
Overlap Width	12cm
Membrane Laying Ways	Membrane laying way by one edge against the other edge
Digital display	function Temperature and speed dual display
Body weight	7.5kg
Warranty	1 year

☎ **Contact Numbers:** +91 8169493708 +91 7893419333 +91 9324847364

✉ **E-Mail Id:** sales@weldinequipments.com , kamran@weldinequipments.com

🌐 **For Information visit our Website:** www.weldinequipments.com