

GEOMEMBRANE WELDER WIN 800D



PRODUCT INFORMATION

Geomembrane Welder WIN 800D

This machine is not only able to show the welding temperature and welding speed, the control system adopts closed loop control, regardless of the external voltage change, or upward or downward direction of welding under the condition of the external environment changes, such as negative feedback automatically adjust the setting temperature and speed, make the welding parameters is more stable, more reliable welding quality.

The welding machine adopts the hot-wedge structure of cash, which is small in size and light in weight. It is suitable for welding all hot-melt materials such as HDPE, LDPE, PVC, EVA, ECB, PP, etc. The product is used in tunnels, subways, water conservancy, farming, Waterproof and anti-seepage projects in landfills, chemical mining, sewage treatment, roof construction and other fields.



SPECIFICATIONS

| | |
|---------------------------|-------------------------------|
| Model | WIN 800D |
| Rated Voltage | 230V/120V |
| Rated Power | 800W/1100W |
| Frequency | 50/60HZ |
| Heating Temperature | 50~450 |
| Welding Speed | 0.5-5m/min |
| Material Thickness Welded | 0.2mm-1.5mm(single layer) |
| Seam Width | 12.5mm*2,Interior Cavity 12mm |
| Weld Strength | ≥85% material |
| Overlap Width | 10cm |
| Digital Display | Yes |
| Body weight | 5kg |
| Warranty | 1 year |
| Certification | CE |

☎ **Contact Numbers:** +91 8169493708 +91 7893419333 +91 9324847364

✉ **E-Mail Id:** sales@weldinequipments.com , kamran@weldinequipments.com

🌐 **For Information visit our Website:** www.weldinequipments.com